



ENERG
енергия · ενεργεια

Y IJA
IE IA

NIBE

NIBE F1126-6



55 °C

35 °C



A++

A++



43 dB



dB



2015

811/2013



ENERG
енергия · ενεργεια

Y IJA
IE IA

NIBE


NIBE F1126-6 + VPB300




55°C




XXL



A++



A



2015

811/2013



ENERG

енергия · ενεργεια

Y

IJA

IE

IA

NIBE

NIBE F1126-6

 35 °C



A⁺⁺

A⁺⁺⁺

A⁺⁺

A⁺⁺

A⁺

A

B

C


D

E

F

G

+



+



+



+





ENERG

енергия · ενέργεια

Y






IJA

IE


IA


NIBE


NIBE F1126-6 + VPB300









XXL

+ 




+ 

+ 



+ 



55 °C


XXL

Supplier's name:	NIBE		
Model:	NIBE F1126-6 (+VPB 300)		
Temperature application	35	55	°C
Declared load profile for water heating	XXL		
Seasonal space heating energy efficiency class, average climate:	A++	A++	
Water heating energy efficiency class, average climate:	A		
Rated heat output, average climate:	7	6	kW
Annual energy consumption for space heating, average climate	3345	3726	kWh
Annual electricity consumption for water heating, average climate	2178		kWh
Seasonal space heating energy efficiency, average climate:	165	125	%
Water heating energy efficiency, average climate:	99		%
Sound power level LWA indoors	43		dB
Rated heat output, cold climate:	7	6	kW
Rated heat output, warm climate:	7	6	kW
Annual energy consumption for space heating, cold climate	3887	4322	kWh
Annual electricity consumption for water heating, cold climate	2178		kWh
Annual energy consumption for space heating, warm climate	2181	2438	kWh
Annual electricity consumption for water heating, warm climate	2178		kWh
Seasonal space heating energy efficiency, cold climate:	170	129	%
Water heating energy efficiency, cold climate:	99		%
Seasonal space heating energy efficiency, warm climate:	163	124	%
Water heating energy efficiency, warm climate:	99		%
Sound power level LWA outdoors	-		dB

Data for package fiche

Controller class	III		
Controller contribution to efficiency	1,5		%
Seasonal space heating energy efficiency of package, average climate:	166	127	%
Seasonal space heating energy efficiency class for package, average climate:	A++	A++	%
Seasonal space heating energy efficiency of package, cold climate:	171	130	%
Seasonal space heating energy efficiency of package, warm climate:	165	125	%

Model(s):		NIBE F1126-6 (+VPB 300)								
Type of heat source/sink:		Brine-to-water								
Low-temperature heat pump:		No								
Equipped with supplementary heater:		Yes								
Heat pump combination heater:		Yes								
Climate condition:		Average								
Temperature application:		Medium temperature (55 °C)								
Applied standards: EN14825 and EN16147										
Rated heat output		Prated	6,0	kW	Seasonal space heating energy efficiency		η_s	125	%	
<i>Declared capacity for part load at outdoor temperature Tj</i>				<i>Declared coefficient of performance for part load at outdoor temperature Tj</i>						
Tj = -7 °C	Pdh	4,2	kW	Tj = -7 °C	COPd	2,90	-			
Tj = +2 °C	Pdh	4,8	kW	Tj = +2 °C	COPd	3,48	-			
Tj = +7 °C	Pdh	5,1	kW	Tj = +7 °C	COPd	3,73	-			
Tj = +12 °C	Pdh	5,4	kW	Tj = +12 °C	COPd	3,93	-			
Tj = biv	Pdh	4,5	kW	Tj = biv	COPd	3,18	-			
Tj = TOL	Pdh	3,9	kW	Tj = TOL	COPd	2,65	-			
Tj = -15 °C (if TOL < -20 °C)	Pdh		kW	Tj = -15 °C (if TOL < -20 °C)	COPd		-			
Bivalent temperature				T _{biv}	-3,5	°C	Operation limit temperature			
Cycling interval capacity for heating				P _{cyh}		kW	Cycling interval efficiency		COP _{cyh}	
Degradation co-efficient				Cdh	0,99	-	Heating water operating limit		WTOL	65
<i>Power consumption in modes other than active mode</i>				<i>Supplementary heater</i>						
Off mode	P _{OFF}	0,002	kW	Rated heat output		P _{sup}	2,1	kW		
Thermostat-off mode	P _{TO}	0,01	kW							
Standby mode	P _{SB}	0,007	kW	Type of energy input		Electric				
Crankcase heater mode	P _{CK}	0,014	kW							
<i>Other items</i>										
Capacity control	fixed			Rated air flow rate, outdoors				m ³ /h		
Sound power level, indoors/outdoors	L _{WA}	43/-	dB	Rated water flow rate, indoor heat exchanger			0,42	m ³ /h		
Annual energy consumption	Q _{HE}	3726	kWh	Rated brine or water flow rate, outdoor heat exchanger			0,73	m ³ /h		
<i>For heat pump combination heater:</i>										
Declared load profile		XXL		Water heating energy efficiency		η_{wh}	99	%		
				Daily electricity consumption		Q _{elec}	9,92	kWh		
				Annual electricity consumption		AEC	2178	kWh		
				Daily fuel consumption		Q _{fuel}		kWh		
				Annual fuel consumption		AFC		GJ		
Approved by:										
Contact details		© NIBE Energy Systems - Box 14 - Hannabadsvägen 5 - 28521 Markaryd - Sweden								